

32" Metal Frame



- 32" Metal Frame
- Resolution 1366 x 768
- Brightness 450cd/m²
- Contrast Ratio 4000:1

Display Panel	Screen Size		32"
	Active Display Area (mm)		697.68(H) x 392.25(V)
	Aspect Ratio		1366 x 768 (WXGA)
	Display Colors		16 : 9
	Brightness (cd/m ²)(typ)		450
	Contrast Ratio		4000 : 1
	Viewing angle (H ⁹ /V ⁹)		178° / 178°
	Bezel Size (U/D/L/R)(mm)		25.8 / 25.8 / 28.2 / 28.2
	Outline Dimension (mm)		760 x 450 x 50.2
	Weight (kg)		6.5
	Life Time		50,000h
Resolution	Monitor		1360 x 768
	DTV		1080i
Connectivity & Control	Input		VGA (15pin D-sub), HDMI, Composite(BNC), Component(BNC), PC Audio, Composite Audio, Component Audio, RS232C
	Output		VGA (15pin D-sub), DVI (Connected type HDMI) -> HDMI (HDCP Not Supported), Composite(BNC), Component(BNC), RS232C, Speaker(Ready)
	Multi-Screen Function (Loop)		HDMI, VGA (15pin D-Sub), Component(BNC), Composite (BNC)
	Power Requirement	Input Voltage	100 - 240VAC
		Consumption (typ)(W)	140
	Auto Cooling System		Yes (1EA)
Auto Power Control (DPMS)		Yes	
Feature	Option	AR Coating	Option
		Tempered Glass	Option
		Optical Bonding	Option
		Touch Screen	Option
		Transflective	Option
		Auto Brightness Control	Option
Mechanical	Dimension (mm)	Set (W x H x L)(mm)	764 x 454 x114.3
		Bezel Size (U/D/L/R) (mm)	30 / 30 / 32 / 32
		Packed (W x H x L)(mm)	908 x 619 x 243
	Weight (kg)	Set / Packed (kg)	19kg / 22.5kg
	Wall Mounting Hole (W x H)(mm)		400 x 200
Approvals	EMI / EMC		FCC, CE, VCCI, KCC
	Safety		CB, TUV, cTUVus
Accessories			Power Cord, HDMI Cable (Option : DVI to HDMI / D-SUB / RS-232C / Audio Cable)
OSD Language			10 Language
Temperature			0℃ - 40℃
Humidity			20% - 80%