


Slim Design Affordable


32"/42"/47"/55"/65" FULL HD DISPLAY LS33A**SLIM DESIGN**

Direct-LED panel featuring slim BLU offers stylishly slim monitors designed to fit perfectly into narrow spaces in retail shops while ensures high energy efficiency

Slim Design


**PORTRAIT/LANDSCAPE MODES**

Portrait/Landscape Scene available

**COST-EFFECTIVE SOLUTION**


SuperSign embedded player is suitable for running simple content in an effort to save cost and ease of installation and maintenance as well

No need for an additional media player

**REMOTE CONTROL VIA RS232C & NETWORK**

SuperSign embedded player with RJ45 interface allows easy content transfer and control via network

Network based content control



LS33A SERIES 32", 42", 47", 55", 65"



FEATURES

- Brightness: 300nit(32"/42"/47"), 330nit(55"), 350nit(65")
- Direct-LED Display
- Portrait/Landscape Orientation
- Embedded Media Player
- Vertical Retail Targets : SMB (Small & Medium Business), Retailers
- Energy Star 6.0 Compliant
- IPS Panel
- Low Screen Temperature
- No Blackening Defect
- Wide Viewing Angle



SPECIFICATIONS

LS33A

PANEL	Screen Size	32", 42", 47", 55", 65"	PHYSICAL SPECIFICATION	Monitor Dimension (W x H x D)	32": 73.0cm x 42.9cm x 5.5cm 42": 96.0cm x 56.0cm x 5.5cm 47": 107.0cm x 62.0cm x 5.58cm 55": 123.8cm x 71.2cm x 5.68cm 65": 146.0cm x 84.0cm x 5.76cm
	Panel Technology	IPS			Weight (Head)
	Native Resolution	Full HD (1920X1080)		Operation Temperature	0 °C to 40 °C
	Brightness	32"/42"/47": 300nit / 55": 330nit / 65": 350nit		Operation Humidity	10 % to 80 %
CONNECTIVITY	Contrast Ratio	32"/42"/47": 1,200:1 / 65": 1,400:1	ENVIRONMENT CONDITIONS	Typical / Smart Energy Saving	33": 45W / 28W 42": 65W / 38W 47": 80W / 65W 55": 85W / 67W 65": 200W / 140W
	Dynamic CR	500,000:1			
	Viewing Angle (H x V)	178 x 178	POWER	STANDARD (CERTIFICATION)	UL / cUL / CB / TUV / KC EMC ErP / Energy Star
	Response Time	9ms(G to G BW)			Slot PC Compatible (optional) External Media player Attachable SuperSign Elite-w lite / Elite-C
PHYSICAL SPECIFICATION	Input (Rear)	Digital HDMI(1) Analog RGB(1) USB Yes(1) Digital - Audio Yes(1) External Control RS232C(1)	MEDIA PLAYER COMPATIBILITY	ACCESSORY	32": No / 42", 47", 55", 65": Yes (MP500/MP700) Yes / Yes
	Output				Remote Controller(include battery 2ea), Power Cord, IR Receiver, CD(Owner's Manual, SuperSign Program / Manual), RGB Cable
	Bezel Width	32": (R/L) 10.5mm(15.1mm for rearmost spot) (T) 10mm(14.6mm for rearmost spot) (B) 14mm(18.6mm for rearmost spot) 42": (R/L/T) 8.5mm(13.3mm for rearmost spot) (B) 14mm(18.8mm for rearmost spot) 47": (R/L/T) 8.5mm(13.2mm for rearmost spot) (B) 14mm(18.7mm for rearmost spot) 55": (R/L/T) 8.5mm(13.2mm for rearmost spot) (B) 14mm(18.7mm for rearmost spot) 65": (R/L/T) 9mm(14mm for rearmost spot) (B) 14.6mm(20mm for rearmost spot)			

DIMENSION (unit: mm)

