

INDOOR DIGITAL SIGNAGE

GENERAL LCD DISPLAY

CLASS	MODEL
46"	D46PM

KEY FEATURES

- Special DOOH LED BLU LCD Panel
- LED BLU, Slim Design
- Power Consumption Reduced at 40% Compared to Normal Display
- Built in Video Wall Function
- Portrait / Landscape Orientation
- High Connectivity
- Remote Control (RS232)



Broadcast your branding with Hyundai Digital Signage!

Thanks to the advanced product design, Hyundai Digital Signage Display meets requirements for various digital signage solutions. Not only take advantage from slim and simple design, but also think more about our future environment, saving energy up to 40 percent. LED technologies bring more than just expected.



SPECIFICATIONS

Model	D46PM	
Panel	Screen Size (diagonal)	46"
	Active Display Area (inch/mm)	47.62 x 26.79 / 1018.08 x 572.67
	Resolution	1920 x 1080
	Aspect Ratio	16:9
	Display Colors	16.7M
	Brightness (cd/m²; typ.)	700
	Contrast Ratio	4000:1
	Viewing Angle	178°/178°
	Lifetime (hours)	50,000
	Backlight type	LED
Resolution	Monitor	1920 x 1080
	DTV	1080p
Input	Video	x1 VGA, x1 HDMI, x1 DVI, x1 RS232, 1x IR
	Audio	1x PC Audio
Output	Video	x1 DVI, x1 RS232, 1x IR
	Audio	Audio Line Out, Speaker L/R
Power	Input Voltage	100 – 240V AC
	Power consumption	90 W (typ)
Features	PIR Sensor (Motion detection)	Option
	Auto Cooling System	no
	Auto Power Control	yes
	Auto Brightness Sensor	yes
Operation	Temperature (°C)	0 - 40
	Humidity (%)	20 - 80
	OSD Language	10 Lang
Dimension	Set (W x H x D) mm	1052.4 x 603.2 x 44
	Bezel Size (U/D/L/R) mm	13.6 / 13.6 / 15.5 / 15.5
	Wall Mounting (WxH), mm	600 / 400 / 300 x 400 / 300
Weight	Set (kg)	21 kg

FEATURES

Special Out-Of-Home LCD Panel

By using commercial grade LCD panels for Out-Of-Home applications, HYUNDAI Digital Signage display can provide higher brightness and contrast than standard LCD TV panels. This guarantees longer working time, deliver clear and bright image contents in the portrait or landscape format without any loss of quality.

LED Backlight

HYUNDAI's public displays with LED backlight bring the advantage of up to 40% lower power consumption, compared to displays with CCFL backlight.

Easy operating OSD menu, Remote control


In order to setup a multi display wall, the single units are linked by a daisy chain connection over DVI interface. The configuration of each display can be easily set-up over the on-screen menu or the RS232C interface.

Slim Design

These products enable the super-slim design.

DIMENSIONS

D46PM [unit: mm]



Specifications and design are subject to change without notice. See our website for detailed information.

HEAD OFFICE - HYUNDAI IBT CO., LTD.

106, Apogongdan-gil, Gimche on-si, Gyeongsangbuk-do,
740-862 The Republic of Korea
Tel. +82 54 430 6426 E-mail: prio123@hyundaiibt.com
www.hyundaiibt.com

HYUNDAI IT AMERICA CORP.

2051 Junction AVE., Suite 112 San Jose, CA 95131, USA
Tel. +1 408 954 8920 email : sales@hyundaait.com
www.hyundaait.com

HYUNDAI IT EUROPE GMBH

Siemensstrasse 22, 63225 Langen, Germany
Tel. +49(0) 6103-38878-100 email : info@hyundaait.eu
www.hyundaait.eu

HYUNDAI IT JAPAN

Kawaziri Bldg 2F, 534 Waseda Tsurumakicho, Shinjuku-ku,
Tokyo, Japan
Tel. +81 70 8628 4437 email : thkim@hyundaait.com
www.hyundaait.com