

# eTILE 22M-II

The eTILE 22 is an ultra-thin interactive all-in-one touch display. Based on Intel® Broadwell technology, this powerful dynamic touch device will enhance the interactive experience. Furthermore it incorporates a Full HD display, Full HD Webcam and port cover to minimize user tampering. Purposely built for 24/7 use in kiosk environments.

- + 5th Generation embedded CPU with support for 4K content playback
- + Handles high operation vibrations for use in harsh environments
- + Tamper resistant because of cable management and hidden keypad



33 mm



## WT22M-FW

<b>Dimensions</b>	526 x 333 x 33 mm (WxHxD)	<b>Touch Panel</b>	PCT (Project Capacitive Touch (10 point touch) Pencil hardness: 7H per ASTM D3363
<b>Weight</b>	6 kg	<b>Security</b>	Hidden keypad Secure cable cover Concealed on/off controls
<b>Storage</b>	Supports 2.5" SATA III HDD/SSD (HDD enclosure not included) and mSATA Default 64G mSATA SSD	<b>System I/O</b>	Audio Line-Out x1 DC Jack x1 Audio Line-In x1 HDMI Out Port 1.4a HDMI x1 USB 2.0 Port x 4 USB 3.0 Port: x 4 RJ45 LAN Jack x1 DC 12V-20V Input x 1 RJ50 Ports x 4 Antenna hole x 2
<b>CPU</b>	Intel® Broadwell CPU i3-5010U	<b>Front Panel</b>	IP65 grade Dust- & Waterproof
<b>Memory</b>	Dual Channel DDR3 2GB x2 Low Voltage DDR 1333 (Max 16G)	<b>Watchdog Timer</b>	1 sec ~ 255 sec
<b>LAN</b>	Single Intel Gigabit Ethernet Intel WGI218LM Mbps 10/100/1000	<b>Accessories</b>	Wall Mount Kit x1 90W Power Adapter x1 Power Cord x1
<b>Audio</b>	HDMI 1.4a Analog 2 channels I/O	<b>Adapter</b>	90W (19.5V, 4.74A) AC Adapter
<b>LCD</b>	Display Size: 21.5" Resolution: 1920 x 1080 (16:9) Maximum Brightness : 250 Nits Viewing angle horizontal: 89/89; Vertical 89/89		

Supports:

