

ADM DT22MT

A 21.5" display with touch capabilities built for the digital signage and POS market to maximize the media entertainment experience and increase customer interaction.

- + Easy installation: no need for an enclosure or kiosk, the ADM display can simply be mounted on, or in the wall using various wall mount solutions
- + Robust VA panel
- + Aesthetics: slim form factor
- + True flat surface: easy to clean
- + Ideal viewing angle for both portrait and landscape mode



ADM DT22MT

Panel Size	21.5"	Power Interface	19V Power Adapter (when powered on less than 36W power consumption, in stand-by mode less than 0.5W power consumption)
Bezel Size	Top Bezel: 25.29mm / Bottom Bezel: 29.5mm Left & Right Bezel: 19.38mm	Signal Connector	DVI-I & VGA Display Interface RS232 I/O Port USB 2.0 Port
Dimensions	516x323x37mm	LCD OSD Settings	Keypad Settings for Brightness & Contrast
Weight	5kg	Audio	Line-in Audio Jack, Internal 2W Speaker
Display	Vertical Alignment (VA) Panel Full HD Display with back light LED design	Surface Treatment	Slim Bezel, True Flat Panel Design, 7H Hardness
Resolution	1920 x 1080	Operating Temperature	0 ~ 50°
VA Panel Brightness	250 Nits	Storage Temperature	-20 ~ 60°
Touch Panel	PCT Multi Touch Surface (10 point touch) Finger & Capacitive Stylus Wake on Touch	Relative Humidity	90% RH
Touch Control Driver	Microsoft Windows & Android Compatible	MTBF	30,000 hours
Optical Response Time	16ms	Certification	CE (including ERP)/FCC/LVD